

APPENDIX A Revision A	TRAILER MOUNTED SUPPORT SYSTEM PRODUCT DATA SHEET	
Company	DHS Systems LLC	
Part Number or NSN	1004868 Model: HP-4/188, Desert Tan, Analog	
Specifications as applicable	•	
Safety and Mobility Certification by Military Test Center		
Trailer	<u> </u>	
Stowage Components included with trailer	NA	
Cargo Volume Stowage, For shelter and accessory components In cubic feet	140 cu. ft.	
Physical Dimensions for trailer	6.5 ft H	
Height	7.2 ft W	
Width	19 ft L	
Length Recommended Prime Mover Vehicle		
Recommended Prime Mover Verlicie	LMTV	Requires a vehicle that can tow a 6,500 lb. trailer.
Empty GVW		
Tongue Weight	260 lb.	
Tire Type and Size	Radial	Two 37 x 12.50 x 16.5 LT Goodyear Wrangler R/T II, Load Rating C bias ply, run-flat tires
Fuel Tank Capacity	16 gal.	
Generator		
Nominal Output in kW, Volts AC, Hertz, Phase	18kW	120/208VAC, 60 Hz, 3-Phase.
Operating Environment	All	Operating Range from -50 °F to +140 °F.
Engine type	Diesel	Four cylinder, liquid cooled, direct injection, 1800 RPM.
Fuel Type	Diesel	Can also use JP8 or JP5.

(

E 10 "	,	
Fuel Consumption	NIA	
(AC Compressor On)	NA	
At 25% load	NA	
At 50% Load	NA	
At 75% Load	1.25	
at maximum output	Gal/hr.	
Noise in DB at 25 feet	1	
(AC Compressor On)	NA	
At 25% load	NA	
At 50% load	NA	
	T .	
At 75% Load	76 dB	
At maximum rated load		
Heater	ı	
Nominal Output in BTU's	NA	
	INA	
Electric Requirement		
Volts/Amps	NA	
		·
Air Conditioning		
Maximum Cooling Capacityin	ı	
	96,000 BTL	
BTU's	00,000 B10	
Maximum Heat Output	0 -4	92,000 BTU/hr electric heat. 80,000 BTU/hr fuel fired AUX heat.
Capacity in BTU's	2 stage nea	92,000 BTO/fil electric fleat. 60,000 BTO/fil fluel lifed AOA fleat.
Refrigerant Type		
Treingerant Type	R407-C	
	11407-0	
CFM Air Flow	<u> </u>	
CFW AII FIOW		
	3,000 CFM	
IA's David Diamenton		
Air Duct Diameter		
	14 inch	Two 14 in. Supply, two 14 in. Return
Power Requirements in kW, VAC, HZ,	2014/4	
Phase	28kW	
		208 VAC, 60 Hz, 3-phase.
		200 1710, 00 112, 0 pilado.
Special/Additional Features:		
populari dataros.	The HP-4/1	88 Trailer provides three primary features for the end user of a larger
		elter - cargo space, environmental control and power. It has a 140
		argo area, includes a 16 gallon fuel tank and comes with an 18 kW
	Genset and	8 Ton ECU.
	INCLUDES	
	INCLUDES:	
	1 Drip Berm (T295188)	
	1 Trailer Electrical Set (T2-95220)	
		,
	1 Trailer Push Package (TR20IS)	
	2 Supply Ducts (T291230)	
	2 Return Ducts (T291432)	
	1 Auxiliary Fuel Kit (T295180)	
	i Auxiliary I	- uei Mit (1730100)